

ジェットミルスレッド MTZタイプ




スパイラル溝内に油穴の付いた新型超硬ソリッドミルスレッド！
冷却液を刃先まで効率よく届け、よりスムーズに加工できます。

特徴

- 特に貫通穴には威力を発揮します。
- 切粉の除去には効果的です。
- 外部給油装置の付いていない機械にも適しています。

ISO



メートル内径ねじ用



ピッチ mm	並目	細目	型番	d mm	D mm	刃数	I mm	L mm	価格
1.0	M6	$\phi \geq 7$	Z06048C10 1.0 ISO	6	4.8	3	10.5	58	¥39,000
1.0		$\phi \geq 9$	Z0606C12 1.0 ISO	6	6.0	3	12.5	58	¥39,000
1.0		$\phi \geq 10$	Z0808D16 1.0 ISO	8	8.0	4	16.5	64	¥45,300
1.25	M8	$\phi \geq 10$	Z0606C14 1.25 ISO	6	6.0	3	14.4	58	¥39,000
1.25	M8	$\phi \geq 10$	Z0606C19 1.25 ISO	6	6.0	3	19.4	58	¥46,700
1.5	M10	$\phi \geq 12$	Z08078C17 1.5 ISO	8	7.8	3	17.0	64	¥45,300
1.5		$\phi \geq 14$	Z1010D21 1.5 ISO	10	10.0	4	21.8	73	¥52,000
1.5		$\phi \geq 16$	Z1212D26 1.5 ISO	12	12.0	4	26.3	84	¥58,700
1.5		$\phi \geq 20$	Z1616E33 1.5 ISO	16	16.0	5	33.8	101	¥78,800
1.75	M12	$\phi \geq 12$	Z1009C20 1.75 ISO	10	9.0	3	20.1	73	¥52,000
1.75	M12	$\phi \geq 12$	Z1009C28 1.75 ISO	10	9.0	3	28.9	73	¥62,500
2.0	M14	$\phi \geq 15$	Z1010C27 2.0 ISO	10	10.0	3	27.0	73	¥52,000
2.0	M16	$\phi \geq 17$	Z12118D27 2.0 ISO	12	11.8	4	27.0	84	¥58,700
2.5	M20	$\phi \geq 22$	Z1615E33 2.5 ISO	16	15.0	5	33.8	101	¥78,800

G(55°)



内外径ねじ共用



山数 (TPI)	標準	型番	d mm	D mm	刃数	I mm	L mm	価格
28	G1/8	Z08078C14 28W	3	7.8	3	14.1	64	¥45,300
19	G1/4-3/8	Z1010D16 19W	10	10.0	4	16.7	73	¥52,000
14	G1/2-7/8	Z1616E26 14W	16	16.0	5	26.3	101	¥78,800
11	G \geq 1	Z1616D38 11W	16	16.0	4	38.1	101	¥78,800

BSPT

内外径ねじ共用



山数 (TPI)	標準	型番	d mm	D mm	刃数	I mm	L mm	価格
28	RC1/8	Z08078C14 28 BSPT	8	7.8	3	14.1	64	¥45,300
19	RC1/4-3/8	Z1010D16 19 BSPT	10	10.0	4	16.7	73	¥52,000
14	RC1/2-7/8	Z1616E26 14 BSPT	16	16.0	5	26.3	101	¥78,800
11	RC1-2	Z1616D28 11 BSPT	16	16.0	4	28.9	101	¥78,800


ピンク色の型番表示は、ノガ・ジャパン在庫品です。

ジェットミルスレッド MTZタイプ

スパイラル溝内の油穴付超硬ソリッドミルスレッド


BSW

内外径ねじ共用




山数 (TPI)	標準	型番	d mm	D mm	刃数	l mm	L mm	価格
20	1/4	Z06046C12 20W	6	4.6	3	12.1	58	¥39,000
18	5/16	Z06053C14 18W	6	5.3	3	14.8	58	¥39,000
16	3/8	Z08068C16 16W	8	6.8	3	16.7	64	¥45,300
16	1/2	Z10092D24 16W	10	9.2	4	24.6	73	¥52,000
14	7/16	Z08078D20 14W	8	7.8	4	20.9	64	¥45,300
12	1/2	Z10086D24 12W	10	8.6	4	24.4	73	¥52,000
11	5/8	Z12109D28 11W	12	10.9	4	28.9	84	¥58,700

※油穴の付いていないカッター。




UN

内径ねじ用




山数 (TPI)	UNC	UNF	UNEF	型番	d mm	D mm	刃数	l mm	L mm	価格
28		1/4		Z0605C11 28 UN	6	5.0	3	11.3	58	¥39,000
28			7/16-1/2	Z0606C14 28 UN	6	6.0	3	14.1	58	¥39,000
24		5/16		Z08066C14 24 UN	8	6.6	3	14.3	64	¥45,300
24		3/8	9/16-5/8	Z0808D21 24 UN	8	8.0	4	20.6	64	¥45,300
20		7/16		Z0808C21 20 UN	8	8.0	3	21.0	64	¥45,300
20		1/2		Z1010D22 20 UN	10	10.0	4	22.3	73	¥52,000
20			3/4-1	Z1212E27 20 UN	12	12.0	5	27.3	84	¥58,700
18	5/16			Z06056C14 18 UN	6	5.6	3	14.8	58	¥39,000
18		9/16-5/8	1 1/8-1 5/8	Z12113D26 18 UN	12	11.3	4	26.1	84	¥58,700
16	3/8			Z08067C16 16 UN	8	6.7	3	16.7	64	¥45,300
16		3/4		Z1212D31 16 UN	12	12.0	4	31.0	84	¥58,700
14	7/16			Z08077C20 14 UN	8	7.7	3	20.9	64	¥45,300
14		7/8		Z1616E37 14 UN	16	16.0	5	37.2	101	¥78,800
13	1/2			Z10092C22 13 UN	10	9.2	3	22.5	73	¥52,000
12	9/16			Z12105C26 12 UN	12	10.5	3	26.5	84	¥58,700
11	5/8			Z12114C28 11 UN	12	11.4	3	28.9	84	¥58,700
10	3/4			Z16144D34 10 UN	16	14.4	4	34.3	101	¥78,800




NPT

内外径ねじ共用




山数 (TPI)	標準	型番	d mm	D mm	刃数	l mm	L mm	価格
27	1/8	Z08076C10 27 NPT	8	7.6	3	10.8	64	¥45,300
18	1/4-3/8	Z1010D16 18 NPT	10	10.0	4	16.2	73	¥52,000
14	1/2-3/4	Z16155D22 14 NPT	16	15.5	4	22.7	101	¥78,800



NPTF

内外径ねじ共用



山数 (TPI)	標準	型番	d mm	D mm	刃数	l mm	L mm	価格
27	1/8	Z08076C10 27 N(PT)F	8	7.6	3	10.8	64	¥45,300
18	1/4-3/8	Z1010D16 18 N(PT)F	10	10.0	4	16.2	73	¥52,000
14	1/2-3/4	Z16155D22 14 N(PT)F	16	15.5	4	22.7	101	¥78,800

